

ELECTROLUMINESCENT DEVICE

CROSS-REFERENCE TO RELATED APPLICATIONS

This is a continuation-in-part of International Application PCT/US00/41086, with an international filing date of October 5, 2000, published in English under PCT Article 21(2), which claims priority to United States Provisional Application Serial No. 60/157,944, filed on October 6, 1999, which hereby are incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a method for making an electroluminescent lamp, and more particularly, to a method for making an electroluminescent lamp wherein the electroluminescent active layer is made by ultraviolet ("UV") light curing.

2. Background Art

A typical electroluminescent lamp is a multilayer thin film structure that emits visible light when activated by an applied voltage. Such electroluminescent lamps have found utility in a number of different applications, such as, backlighting for cell phones, backlighting for hand held personal organizers, lighting for point of purchase displays, and backlighting for automotive dash boards.

The active layer (hereafter referred to as the "electroluminescent active layer") is the layer in an electroluminescent lamp which actually emits the light produced by such a device. The electroluminescent active layer will often contain a phosphor. This electroluminescent active layer has previously been deposited by applying various curable compositions to a substrate. However, the

compositions typically contain organic solvents that do not incorporate into the electroluminescent active layer after curing. Such solvent-based systems are undesirable because of the hazards and expenses associated with volatile organic solvents. Furthermore, these solvent-containing compositions often produce layers
5 marred by defects and decreased film quality.

In a typical electroluminescent lamp, the active layer comprises one layer of a multilayer electroluminescent device. An example of such a device would contain a substrate made of polycarbonate or glass coated with a transparent conductor such as fluorine doped tin oxide or indium tin oxide. Metallic grid lines
10 are patterned onto the substrate. The active layer is then applied by screen printing the electroluminescent composition onto the substrate with gridlines. A dielectric coating is then optionally applied over the structure. Finally, the device is coated with a metallic backing. The active layer in such electroluminescent devices typically contains a phosphor. Such various oxide or nitride phosphors may or may
15 not be encapsulated with silica. Encapsulation protects the phosphor from deleterious environmental effects.

Electroluminescent lamps in addition to the electroluminescent active layer often include an opaque conductive layer, a dielectric layer, and a transparent conductive layer. Typically, such layers have been made by a number of thin film
20 processes, which include, chemical vapor deposition, thermal curing, sputtering, thermal dip coating, and evaporation. Fabrication of an electroluminescent lamp where each layer is fabricated by a single type of process is desirable.

Many thin layers, such as the electroluminescent active layer used in an electroluminescent lamp, are often made from compositions that are cured by
25 heat. These heat curable compositions require the use of organic solvents that contain a significant amount of volatile organic compounds (VOCs). These VOCs escape into the atmosphere while the heat curable composition dries. Such solvent-based systems are undesirable because of the hazards and expenses associated with VOCs. The hazards include water and air pollution and the expenses include the
30 cost of complying with strict government regulation on solvent emission levels. In

contrast, UV curable compositions contain reactive monomers instead of solvents, thus eliminating the detrimental effects of the VOCs.

The use of heat curable compositions not only raises environmental concerns but other disadvantages exist with their use as well. Heat curable compositions suffer from slow cure times that lead to decreased productivity. These compositions require high energy for curing due to energy loss as well as the energy required to heat the substrate. Additionally, many heat curable compositions yield poor film properties that result in decreased value of the end product.

UV curing is an alternative to heat curing. UV curable compositions are typically applied to a substrate through spraying, screen printing, dipping or brushing for the protection or decoration of the substrate. In the usual application, a substrate such as metals, glass, or plastics is coated with the composition and then UV light is introduced to complete the curing process. The UV curable compositions offer many advantages over typical heat curable compositions.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an improved method for forming an electroluminescent lamp wherein the electroluminescent active layer is formed by UV curing.

It is another object of the present invention to provide an improved method for forming a multilayer electroluminescent lamp wherein each layer is formed by UV curing.

It is still another object of the present invention to provide an improved dielectric composition that is capable of being used in an electroluminescent lamp.

It is yet another object of the present invention to provide an improved UV curable dielectric composition useful for forming a dielectric layer

wherein the dielectric composition does not contain any significant amount of volatile organic solvents that do not become incorporated in the dielectric layer after the dielectric composition is cured

5 The present invention discloses a method for forming an electroluminescent lamp on a substrate. The method of the present invention includes a sequence of steps in which an electroluminescent active layer is formed from a UV curable electroluminescent composition. This sequence of steps comprises:

- 10 a) applying an electroluminescent composition wherein the electroluminescent composition has the characteristic of being curable into an electroluminescent active layer when irradiated with UV light; and
- b) curing the electroluminescent composition with UV light for a sufficient time to form the electroluminescent active layer.

15 The electroluminescent composition does not contain any significant amount of volatile organic solvents that do not become incorporated in the electroluminescent active layer after curing. Specifically, the electroluminescent composition contains 5% or less volatile, and preferably zero, organic solvents by weight. It is an advantage of the present invention that the deposition of a dielectric layer in an electroluminescent device is optional when the disclosed electroluminescent composition is used to deposit the electroluminescent active layer.

20

In an embodiment of the present invention a method for making an electroluminescent lamp that includes an electroluminescent active layer is provided.

25 The method comprises:

- a) applying a first conductive layer to a substrate;
- b) applying a light-producing layer to the first conductive layer; and
- c) applying a second conductive layer to the light-producing layer.
- 30

The first conductive layer is either an opaque conductive layer or a transparent conductive layer. Similarly, the second conductive layer is also either an opaque conductive layer or a transparent conductive layer. However, the first conductive layer and the second conductive layer are not both opaque conductive layers. The light-producing layer is either an electroluminescent layer or a multilayer construction which includes an electroluminescent layer. The electroluminescent layer is formed by:

- a) applying an electroluminescent composition to a substrate coated with one or more layers wherein the electroluminescent composition has the characteristic of being curable into an electroluminescent active layer when irradiated with UV light; and
- b) curing the electroluminescent composition with UV light for a sufficient time to form the electroluminescent active layer.

The following examples provide preferred configurations for the light-producing layer:

1. an electroluminescent active layer;
2. a multilayer construction comprising a dielectric layer and an electroluminescent active layer wherein the dielectric layer is applied to the first conductive layer before the electroluminescent active layer is applied; or
3. a multilayer construction comprising a dielectric layer and the electroluminescent active layer wherein the electroluminescent active layer is applied to the first conductive layer before the dielectric layer is applied;

In another embodiment of the present invention a method for making an electroluminescent lamp that includes an electroluminescent active layer is provided. The method comprises:

- a) applying an opaque conductive layer to a substrate;
- b) applying an electroluminescent composition to the opaque conductive layer wherein the electroluminescent composition has the characteristic

of being curable into an electroluminescent active layer when irradiated with UV light;

- 5 c) curing the electroluminescent composition applied to the opaque conductive layer with UV light for a sufficient time to form the electroluminescent active layer;
- d) applying a dielectric layer to the electroluminescent active layer; and
- e) applying a transparent conductive layer to the dielectric layer.

10 In another embodiment of the present invention a method for making an electroluminescent lamp that includes an electroluminescent active layer is provided. The method comprises:

- a) applying an opaque conductive layer to a substrate;
- b) applying an electroluminescent composition to the opaque conductive layer wherein the electroluminescent composition has the characteristic
15 of being curable into an electroluminescent active layer when irradiated with UV light;
- c) curing the electroluminescent composition applied to the opaque conductive layer with UV light for a sufficient time to form the electroluminescent active layer; and
- 20 d) applying a transparent conductive layer to the electroluminescent active layer.

 In another embodiment of the present invention a method for making an electroluminescent lamp that includes an electroluminescent active layer is provided. The method comprises:

- 25 a) applying a transparent conductive layer to a substrate;
- b) applying an electroluminescent composition to the transparent conductive layer wherein the electroluminescent composition has the characteristic of being curable into an electroluminescent active layer when irradiated with UV light;

c) curing the electroluminescent composition applied to the transparent conductive layer with UV light for a sufficient time to form the electroluminescent active layer; and

5 d) applying an opaque conductive layer to the electroluminescent active layer.

In another embodiment of the present invention a method for making an electroluminescent lamp that includes an electroluminescent active layer is provided. The method comprises:

10 a) applying a transparent conductive layer to a substrate;
b) applying an electroluminescent composition to the transparent conductive layer wherein the electroluminescent composition has the characteristic of being curable into an electroluminescent active layer when irradiated with UV light;

15 c) curing the electroluminescent composition applied to the transparent conductive layer with UV light for a sufficient time to form the electroluminescent active layer;

d) applying a dielectric layer to the electroluminescent active layer; and

e) applying an opaque conductive layer to the dielectric layer.

20 In yet another embodiment of the present invention a method for making an electroluminescent lamp that includes an electroluminescent active layer is provided. The method comprises:

25 a) applying an opaque conductive layer to a substrate;
b) applying a dielectric layer to the opaque conductive layer;
c) applying an electroluminescent composition to the dielectric layer wherein the electroluminescent composition has the characteristic of being curable into an electroluminescent active layer when irradiated with UV light;

30 d) curing the electroluminescent composition applied to the conductive layer with UV light for a sufficient time to form the electroluminescent active layer; and

e) applying a transparent conductive layer to the electroluminescent layer.

In still another embodiment of the present invention a method for making an electroluminescent lamp that includes an electroluminescent active layer is provided. The method comprises:

- a) applying an opaque conductive layer to a substrate;
- b) applying a dielectric layer to the opaque conductive layer;
- c) applying an electroluminescent composition to the dielectric layer wherein the electroluminescent composition has the characteristic of being curable into an electroluminescent active layer when irradiated with UV light;
- d) curing the electroluminescent composition applied to the dielectric layer with UV light for a sufficient time to form the electroluminescent active layer; and
- e) applying a transparent conductive layer to the electroluminescent active layer.

In still another embodiment of the present invention, an ultraviolet light curable dielectric composition and method for making such a composition is disclosed. The disclosed composition does not contain any significant amount of volatile organic solvents that do not become incorporated in the dielectric layer after curing. Specifically, the dielectric composition contains 5% or less, and preferably zero, volatile organic solvents by weight.

The dielectric composition comprises a photocurable mixture, a photoinitiator, and dielectric material. The photocurable mixture comprises at least one aliphatic acrylated oligomer, wherein the at least one acrylated oligomer is present in an amount of about 10% to 40% of total weight of the dielectric composition. The photocurable mixture of the dielectric composition preferably further comprises an isobornyl acrylate monomer in an amount of about 5% to 30% of the total weight of the dielectric composition, an optional adhesion promoter in an amount of 1% to 10% of total weight of the dielectric composition, and an optional flow promoting agent in an amount of about 0.1% to 6% of total weight

of the dielectric composition. The dielectric composition also includes a photoinitiator in an amount of about 0.5% to 10% of the dielectric composition, and dielectric material in an amount of 30% to 80% of the total weight of the dielectric composition.

5 In accordance with yet another aspect of the invention, a method is provided for depositing a dielectric coating on a substrate. The method comprises a first step of applying to a substrate the dielectric composition set forth above. The method also includes a second step of irradiating the dielectric composition on the substrate with an ultraviolet light to cause the electroluminescent composition to
10 cure into the electroluminescent coating.

In accordance with this method, the dielectric composition can be selectively deposited on the substrate at specific locations where dielectric plating is desired. It need not be applied to the entire substrate.

BRIEF DESCRIPTION OF THE DRAWINGS

15 FIGURE 1 is a schematic of a preferred three layer electroluminescent lamp made by the method of the present invention.

FIGURE 2 is a schematic of a preferred three layer electroluminescent lamp made by the method of the present invention.

20 FIGURE 3 is a schematic of a preferred four layer electroluminescent lamp made by the method of the present invention.

FIGURE 4 is a schematic of a preferred four layer electroluminescent lamp made by the method of the present invention.

FIGURE 5 is a schematic of a preferred four layer electroluminescent lamp made by the method of the present invention.

FIGURE 6 is a schematic of a preferred four layer electroluminescent lamp made by the method of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

Reference will now be made in detail to presently preferred compositions or embodiments and methods of the invention, which constitute the best modes of practicing the invention presently known to the inventor.

All percentages of each of the UV curable compositions as expressed in this document refer to the weight percentage of the stated component to the total weight of that particular composition.

The present invention discloses a method for forming an electroluminescent lamp on a substrate. The method of the present invention includes a sequence of steps in which an electroluminescent active layer is formed from a UV curable electroluminescent composition. This sequence of steps comprises:

- 1) applying an electroluminescent composition to a substrate coated with one or more layers wherein the electroluminescent composition has the characteristic of being curable into an electroluminescent active layer when irradiated with UV light; and
- 2) curing the electroluminescent composition with UV light for a sufficient time to form the electroluminescent active layer.

In an embodiment of the present invention a method for making an electroluminescent lamp that includes an electroluminescent active layer is provided. The method comprises:

- a) applying a first conductive layer to a substrate;
- b) applying a light-producing layer to the first conductive layer; and
- c) applying a second conductive layer to the light-producing layer.

The first conductive layer is either an opaque conductive layer or a transparent conductive layer. Similarly, the second conductive layer is also either an opaque conductive layer or a transparent conductive layer. An opaque conductive layer is a layer which conducts electricity but blocks visible light from passing through.

- 5 Preferably, an opaque conductive layer will block at least 80% of the visible light. A transparent conductive layer conducts electricity and allows visible light to pass through. Preferably a transparent conductive layer will allow at least 20% of the visible light pass through. The first conductive layer and the second conductive layer cannot both be opaque conductive layers. However, both of these layers may
- 10 be transparent conductive layers. Furthermore, when the method of the present invention produces a structure with an electroluminescent active layer sandwiched between an opaque conductive layer and a dielectric layer, the dielectric layer preferably will be capable of transmitting at least 20% of the visible that impinges on this layer.

- 15 The light-producing layer is either an electroluminescent layer or a multilayer construction which includes an electroluminescent layer. The electroluminescent layer is formed by:

- 20 1) applying an electroluminescent composition to a substrate coated with one or more layers wherein the electroluminescent composition has the characteristic of being curable into an electroluminescent active layer when irradiated with UV light; and
- 2) curing the electroluminescent composition with UV light for a sufficient time to form the electroluminescent active layer.

- 25 The following examples provide preferred configurations for the light-producing layer:

- 30 1. an electroluminescent active layer;
2. a multilayer construction comprising a dielectric layer and an electroluminescent active layer wherein the dielectric layer is applied to the first conductive layer before the electroluminescent active layer is applied;
- or

3. a multilayer construction comprising a dielectric layer and the electroluminescent active layer wherein the electroluminescent active layer is applied to the first conductive layer before the dielectric layer is applied;

5 Finally, the entire electroluminescent lamp of the present invention including the substrate may be optionally coated by the process comprising:

- 1) applying a clear-coat composition to the electroluminescent active lamp of the present invention wherein the clear-coat composition is capable of being cured into the dielectric coating when irradiated with UV light; and
- 10 2) curing the clear-coat composition applied to the electroluminescent lamp with UV light for a sufficient time to form the clear-coat coating.

The only requirement of the clear-coat coating is that it transmits light and be
15 capable of protecting the electroluminescent lamp from environmental degradation. Preferably, the clear-coat layer will transmit at least 20% visible light and more preferably at least 50% visible light. Preferably, the clear-coat layer will be from 0.3 to 5.0 mil thick and more preferably from 0.5 to 1.0 mil thick.

1. Method of forming the three layer electroluminescent lamp of Figure 1.

20 With reference to Figure 1, electroluminescent lamp 2 formed on substrate 4 is described. Electroluminescent lamp 2 comprises opaque conductive layer 6, electroluminescent active layer 8, and transparent conductive layer 10. Opaque conductive layer 6 is disposed over substrate 4. Electroluminescent active layer 8 is in turn disposed over opaque conductive layer 6. Finally, transparent
25 conductive layer 10 is disposed over electroluminescent layer 8. In a first particularly preferred embodiment of the present invention, a method for making an electroluminescent lamp illustrated in Figure 1 is provided. The method comprises:

- a) applying an opaque conductive layer to a substrate;

b) applying an electroluminescent composition to the opaque conductive layer wherein the electroluminescent composition has the characteristic of being curable into an electroluminescent active layer when irradiated with UV light;

5 c) curing the electroluminescent composition applied to the opaque conductive layer with UV light for a sufficient time to form the electroluminescent active layer; and

d) applying a transparent conductive layer to the electroluminescent active layer.

10 The step of applying an opaque conductive layer to the substrate of this embodiment includes the application of opaque conductive compositions to the substrate that are either thermally curable or photocurable. Preferably the step of applying the opaque conductive layer to the substrate comprises:

15 a) applying an opaque conductive composition to the substrate wherein the opaque conductive composition is capable of being cured into the opaque conductive layer when irradiated with UV light; and

20 b) curing the opaque conductive composition applied to the substrate with UV light for a sufficient time to form the opaque conductive layer.

The step of applying a transparent conductive layer to the electroluminescent active layer of this embodiment includes the application of transparent conductive compositions that are either thermally curable or photocurable. The preferred transparent compositions are UV curable. Preferably
25 the step of applying a transparent conductive layer to the electroluminescent active layer comprises:

30 a) applying a transparent conductive composition to the electroluminescent active layer wherein the conductive composition is capable of being cured into the transparent conductive layer when irradiated with UV light; and

- b) curing the transparent conductive composition applied to the electroluminescent active layer with UV light for a sufficient time to form the transparent conductive layer.

2. Method for forming the three layer electroluminescent lamp of Figure 2

- 5 With reference to Figure 2, electroluminescent lamp 2 formed on substrate 4 is described. Electroluminescent lamp 2 comprise opaque conductive layer 6, electroluminescent active layer 8, and transparent conductive layer 10. Transparent conductive layer 10 is disposed over substrate 4. Electroluminescent active layer 8 is in turn disposed over transparent conductive layer 10. Finally,
- 10 Opaque conductive layer 6 is disposed over electroluminescent layer 8. In a second particularly preferred embodiment of the present invention a method for making an electroluminescent lamp illustrated in Figure 2 is provided. The method comprises:
- a) applying a transparent conductive layer to a substrate;
 - b) applying an electroluminescent composition to the transparent
 - 15 conductive layer wherein the electroluminescent composition has the characteristic of being curable into an electroluminescent active layer when irradiated with UV light;
 - c) curing the electroluminescent composition applied to the transparent conductive layer with UV light for a sufficient time to form the
 - 20 electroluminescent active layer; and
 - d) applying an opaque conductive layer to the electroluminescent active layer.

- 25 The step of applying a transparent conductive layer to a substrate of this embodiment includes the application of transparent conductive compositions that are either thermally curable or photocurable. The preferred transparent compositions are UV curable. Preferably the step of applying a transparent conductive layer to a substrate comprises:

- a) applying a transparent conductive composition to a substrate wherein the conductive composition is capable of being

cured into the transparent conductive layer when irradiated with UV light; and

- b) curing the transparent conductive composition applied to the substrate with UV light for a sufficient time to form the transparent conductive layer.

5

The step of applying an opaque conductive layer to the electroluminescent active layer of this embodiment includes the application of opaque conductive compositions that are either thermally curable or photocurable. The preferred opaque conductive compositions are UV curable. Preferably the step of applying the opaque conductive layer comprises:

10

- a) applying an opaque conductive composition to the electroluminescent active layer wherein the opaque conductive composition is capable of being cured into the opaque conductive layer when irradiated with UV light; and
- b) curing the opaque conductive composition applied to the electroluminescent active layer with UV light for a sufficient time to form the opaque conductive layer.

15

3. Method for forming the four layer electroluminescent lamp of Figure 3

With reference to Figure 3, electroluminescent lamp 2 formed on substrate 4 is described. Electroluminescent lamp 2 comprise opaque conductive layer 6, electroluminescent active layer 8, dielectric layer 12, and transparent conductive layer 10. Opaque conductive layer 6 is disposed over substrate 4. Electroluminescent active layer 8 is in turn disposed over opaque conductive layer 6. Dielectric layer 12 is disposed over electroluminescent layer 8. Finally, transparent conductive layer 10 is disposed over dielectric layer 12. In another embodiment of the present invention a method for making an electroluminescent lamp illustrated in Figure 3 is provided. The method comprises:

20

25

30

- a) applying an opaque conductive layer to a substrate;
- b) applying an electroluminescent composition to the opaque conductive layer wherein the electroluminescent composition has the characteristic

of being curable into an electroluminescent active layer when irradiated with UV light;

- 5 c) curing the electroluminescent composition applied to the opaque conductive layer with UV light for a sufficient time to form the electroluminescent active layer;
- d) applying a dielectric layer to the electroluminescent active layer; and
- e) applying a transparent conductive layer to the dielectric layer.

10 The step of applying an opaque conductive layer to a substrate of this embodiment includes the application of opaque conductive compositions to the substrate that are either thermally curable or photocurable. The preferred opaque conductive compositions are UV curable. Preferably the step of applying the opaque conductive layer to the substrate comprises:

- 15 a) applying an opaque conductive composition to the substrate wherein the opaque conductive composition is capable of being cured into the opaque conductive layer when irradiated with UV light; and
 - b) curing the opaque conductive composition applied to the substrate with UV light for a sufficient time to form the opaque conductive layer.
- 20

25 The step of applying a dielectric layer to the electroluminescent active layer of this embodiment includes the application of dielectric compositions that are either thermally curable or photocurable. The preferred electroluminescent compositions are UV curable. Preferably the step of applying a dielectric layer to the electroluminescent active layer comprises:

- a) applying a dielectric composition to the electroluminescent active layer wherein the dielectric composition is capable of being cured into the dielectric layer when irradiated with UV light; and

- b) curing the dielectric composition applied to the electroluminescent layer with UV light for a sufficient time to form the dielectric layer.

5 The step of applying a transparent conductive layer to the dielectric layer of this embodiment includes the application of transparent conductive compositions that are either thermally curable or photocurable. The preferred transparent compositions are UV curable. Preferably the step of applying a transparent conductive layer to the dielectric layer comprises:

- 10 a) applying a transparent conductive composition to the dielectric layer wherein the conductive composition is capable of being cured into the transparent conductive layer when irradiated with UV light; and
- b) curing the transparent conductive composition applied to the dielectric layer with UV light for a sufficient time to form the transparent conductive layer.

4. Method for forming the four layer electroluminescent lamp of Figure 4.

20 With reference to Figure 4, electroluminescent lamp 2 formed on substrate 4 is described. Electroluminescent lamp 2 comprises transparent conductive layer 10, electroluminescent active layer 8, dielectric layer 12, and opaque conductive layer 6. Transparent conductive layer 10 is disposed over substrate 4. Electroluminescent active layer 8 is in turn disposed over transparent conductive layer 10. Dielectric layer 12 is disposed over electroluminescent layer 8. Finally, Opaque conductive layer 6 is disposed over dielectric layer 12. In another embodiment of the present invention, a method for forming an electroluminescent lamp illustrated in Figure 4 is provided. The method of this embodiment comprises:

- a) applying a transparent conductive layer to a substrate;
- b) applying an electroluminescent composition to the transparent conductive layer wherein the electroluminescent composition has the characteristic

of being curable into an electroluminescent active layer when irradiated with UV light;

- 5 c) curing the electroluminescent composition applied to the transparent conductive layer with UV light for a sufficient time to form the electroluminescent active layer;
- d) applying a dielectric layer to the electroluminescent active layer; and
- e) applying an opaque conductive layer to the dielectric layer.

10 The step of applying a transparent conductive layer to the substrate of this embodiment includes the application of transparent conductive compositions that are either thermally curable or photocurable. The preferred transparent conductive compositions are UV curable. Preferably the step of applying a transparent conductive layer of this embodiment comprises:

- 15 a) applying a transparent conductive composition to substrate wherein the conductive composition is capable of being cured into the transparent conductive layer when irradiated with UV light; and
 - b) curing the transparent conductive composition applied to the substrate with UV light for a sufficient time to form the transparent conductive layer.
- 20

The step of applying a dielectric layer to the electroluminescent active layer of this embodiment includes the application of dielectric compositions that are either thermally curable or photocurable. The preferred electroluminescent compositions are UV curable. Preferably the step of applying a dielectric layer to the electroluminescent active layer of this embodiment comprises:

25

- a) applying a dielectric composition to the electroluminescent active layer wherein the dielectric composition is capable of being cured into the dielectric layer when irradiated with UV light; and

- b) curing the dielectric composition applied to the electroluminescent layer with UV light for a sufficient time to form the dielectric layer.

5 The step of applying an opaque conductive layer to the electroluminescent active layer of this embodiment includes the application of opaque conductive compositions to the substrate that are either thermally curable or photocurable. The preferred opaque conductive compositions are UV curable and are provided below. Preferably the step of applying the opaque conductive layer comprises:

- 10 a) applying an opaque conductive composition to the electroluminescent active layer wherein the opaque conductive composition is capable of being cured into the conductive layer when irradiated with UV light; and
- 15 b) curing the opaque conductive composition applied to the electroluminescent active layer with UV light for a sufficient time to form the opaque conductive layer.

5. Method for forming the four layer electroluminescent lamp of Figure 5.

20 With reference to Figure 5, electroluminescent lamp 2 formed on substrate 4 is described. Electroluminescent lamp 2 comprise opaque conductive layer 6, dielectric layer 12, electroluminescent active layer 8, and transparent conductive layer 10. Opaque conductive layer 6 is disposed over substrate 4. Dielectric layer 12 is in turn disposed over opaque conductive layer 6. Electroluminescent active layer 8 is disposed over dielectric layer 12. Finally, transparent conductive layer 10 is disposed over electroluminescent active layer 8.

25 In yet another embodiment of the present invention, a method for forming an electroluminescent lamp illustrated in Figure 5 is provided. The method of this embodiment comprises:

- a) applying an opaque conductive layer to a substrate;
- b) applying a dielectric layer to the opaque conductive layer;

c) applying an electroluminescent composition to the dielectric layer wherein the electroluminescent composition has the characteristic of being curable into an electroluminescent active layer when irradiated with UV light;

5 d) curing the electroluminescent composition applied to the dielectric layer with UV light for a sufficient time to form the electroluminescent active layer; and

e) applying a transparent conductive layer to the electroluminescent active layer.

10 The step of applying an opaque conductive layer to the substrate of this embodiment includes the application of conductive compositions to the substrate that are either thermally curable or photocurable. The preferred conductive compositions are UV curable. Preferably the step of applying the conductive layer to the substrate of this embodiment comprises:

15 a) applying a opaque conductive composition to the substrate wherein the opaque conductive composition is capable of being cured into the conductive layer when irradiated with UV light; and

20 b) curing the opaque conductive composition applied to the substrate with UV light for a sufficient time to form the conductive layer.

25 The step of applying a dielectric layer to the opaque conductive layer of this embodiment includes the application of dielectric compositions that are either thermally curable or photocurable. The preferred electroluminescent compositions are UV curable. Preferably the step of applying a dielectric layer of this embodiment comprises:

a) applying a dielectric composition to the opaque conductive layer wherein the dielectric composition is capable of being cured into the dielectric layer when irradiated with UV light; and

- b) curing the dielectric composition applied to the opaque conductive layer with UV light for a sufficient time to form the dielectric layer.

5 The step of applying a transparent conductive layer to the electroluminescent active layer of this embodiment includes the application of transparent conductive compositions that are either thermally curable or photocurable. The preferred transparent conductive compositions are UV curable and provided. Preferably the step of applying a transparent conductive layer to the electroluminescent active layer of this embodiment comprises:

- 10 a) applying a transparent conductive composition to the electroluminescent active layer wherein the conductive composition is capable of being cured into the second conductive layer when irradiated with UV light; and
- 15 b) curing the transparent conductive composition applied to the electroluminescent active layer with UV light for a sufficient time to form the second conductive layer.

6. Method for forming the four layer electroluminescent lamp of Figure 6.

20 With reference to Figure 6, electroluminescent lamp 2 formed on substrate 4 is described. Electroluminescent lamp 2 comprise transparent conductive layer 10, electroluminescent active layer 8, dielectric layer 12, and opaque conductive layer 6. Transparent conductive layer 10 is disposed over substrate 4. Dielectric layer 12 is in turn disposed over transparent conductive layer 10. Electroluminescent active layer 8 is disposed over dielectric layer 12. Finally, 25 opaque conductive layer 6 is disposed over electroluminescent active layer 8. In still another embodiment of the present invention, a method for forming an electroluminescent lamp on a substrate is provided. The method of this embodiment comprises:

- 30 a) applying a transparent conductive layer to a substrate;
- b) applying a dielectric layer to the transparent conductive layer;

c) applying an electroluminescent composition to the dielectric layer wherein the electroluminescent composition has the characteristic of being curable into an electroluminescent active layer when irradiated with UV light;

5 d) curing the electroluminescent composition applied to the conductive layer with UV light for a sufficient time to form the electroluminescent active layer; and

e) applying an opaque conductive layer to the electroluminescent active layer.

10 The step of applying a transparent conductive layer to the substrate of this embodiment includes the application of transparent conductive compositions that are either thermally curable or photocurable. The preferred transparent conductive compositions are UV curable. Preferably the step of applying a transparent conductive layer to the substrate of this embodiment comprises:

15 a) applying a transparent conductive composition to the substrate wherein the conductive composition is capable of being cured into the second conductive layer when irradiated with UV light; and

20 b) curing the transparent conductive composition applied to the substrate with UV light for a sufficient time to form the second conductive layer.

25 The step of applying a dielectric layer to the transparent conductive layer of this embodiment includes the application of dielectric compositions that are either thermally curable or photocurable. The preferred electroluminescent compositions are UV curable. Preferably the step of applying a dielectric layer to the transparent conductive layer of this embodiment comprises:

a) applying a dielectric composition to the transparent conductive layer wherein the dielectric composition is capable of being cured into the dielectric layer when irradiated with UV light; and

- b) curing the dielectric composition applied to the transparent conductive layer with UV light for a sufficient time to form the dielectric layer.

5 The step of applying an opaque conductive layer to the electroluminescent active layer of this embodiment includes the application of conductive compositions to the electroluminescent active layer that are either thermally curable or photocurable. The preferred conductive compositions are UV curable. Preferably the step of applying an opaque conductive layer to the electroluminescent active layer of this embodiment comprises:

- 10 a) applying an opaque conductive composition to the electroluminescent active layer wherein the opaque conductive composition is capable of being cured into the opaque conductive layer when irradiated with UV light; and
- 15 b) curing the opaque conductive composition applied to the electroluminescent active layer with UV light for a sufficient time to form the opaque conductive layer.

Preferred substrates for forming the electroluminescent lamp by the various embodiments of the present invention include but are not limited to polyester, cardboard, epoxy coated metal, urethane coated metal, indium tin oxide (ITO) sputtered polyester, fabric, and coated. It will be recognized by those skilled in the art that the method of the present invention can be applied to a number of different substrates.

25 Preferred UV curable compositions for forming the electroluminescent active layer, the opaque conductive layer, the transparent conductive layer, the dielectric layer, and the clear-coat layer are disclosed below. The preferred transparent conductive compositions have been disclosed in International Patent Application, WO0151567 A1, filed Jan. 11, 2001, and published July 19, 2001, hereby incorporated by reference. The preferred transparent conductive compositions have been disclosed in U.S. Patent No.

6,290,881, hereby incorporated by reference. Preferred clear-coat compositions have been disclosed as the woodcoat compositions in International Patent Application, WO0151533 A1, filed Jan. 11, 2001, and published July 19, 2001, hereby incorporated by reference. Each of the preferred UV curable compositions
5 do not contain any significant amount of volatile organic solvents that do not become incorporated in the formed layer after curing. Specifically, each composition contains 5% or less volatile organic solvents by weight. Furthermore, each of these UV curable compositions may be applied to the substrate using a number of different techniques. The compositions may be applied, for example, by
10 direct brush application, or it may be sprayed onto the substrate surface. It also may be applied using a screen printing technique. In such screen printing technique, a "screen" as the term is used in the screen printing industry is used to regulate the flow of liquid composition onto the substrate surface. The compositions typically would be applied to the screen as the latter contacts the substrate. The composition
15 flows through the silk screen to the substrate, whereupon it adheres to the substrate at the desired film thickness. Screen printing techniques suitable for this purpose include known techniques, but wherein the process is adjusted in ways known to persons of ordinary skill in the art to accommodate the viscosity, flowability, and other properties of the liquid-phase composition, the substrate and its surface
20 properties, etc. Flexographic techniques, for example, using pinch rollers to contact the electroluminescent composition with a rolling substrate, also may be used.

The thickness of the various layers of the electroluminescent lamp is adjusted by varying the amounts of the specific UV curable composition which is applied. Preferably, the thickness of the opaque conductive layer is from 0.3 to 1.5
25 mil and more preferably from 0.3 to 1.0 mil thick. The thickness of the dielectric layer is preferably from 0.3 to 2.5 mil and more preferably from 0.3 to 1.0 mil. The thickness of the electroluminescent active layer is preferably from .3 to 2.5 mil and more preferably from 1.0 to 2.0 mil. Finally, the thickness of the transparent conductive layer is from 0.3 to 1.5 mil and more preferably from 0.5 to 1.0 mil.

The UV curable compositions are cured by exposure to UV radiation. This illumination may be carried out in any number of ways known to one skilled in the art, provided the ultraviolet light or radiation impinges upon the UV curable composition so that the composition is caused to polymerize to form the coating, layer, film, etc., and thereby cures.

Various ultraviolet light sources may be used and will be known to one skilled in the art, depending on the application. Preferred ultraviolet radiation sources for a number of applications include known ultraviolet lighting equipment with energy intensity settings of, for example, 125 watts, 200 watts, and 300 watts per square inch. Preferably the UV curable compositions used in the present invention will be cured within 0.5 to 10 seconds of curing time, more preferably within 1.0 to 5 seconds, and most preferably about 2 seconds.

Compositions for Forming the Electroluminescent Active Layer

The electroluminescent active layer is preferably formed by applying an electroluminescent composition to a substrate followed by curing with UV light. The electroluminescent composition comprises an electroluminescent phosphor, a photocurable mixture, and a photoinitiator.

The electroluminescent phosphor is preferably a copper activated zinc sulfide or nitride phosphor. The copper activated zinc sulfide phosphor is preferably present in an amount of about 28% to 80% of the electroluminescent composition. The copper activated zinc sulfide or nitride phosphor may either be encapsulated or unencapsulated. In one particularly preferred embodiment of the present composition the copper activated zinc sulfide or nitride phosphor is present in an amount of about 33%. In another particularly preferred embodiment of the present invention, the electroluminescent phosphor is a mixture of an encapsulated and unencapsulated phosphor present in a total amount of about 80% of the weight

of the electroluminescent composition wherein the encapsulated phosphor is about 50% of the electroluminescent composition and the unencapsulated phosphor is about 25% of the electroluminescent composition. Suitable encapsulated electroluminescent phosphors include ICEGLO 400, ICEGLO 600, TNE 100, TNE 120, TNE 200 TNE 210, TNE 220, TNE 230, TNE 300, TNE 310, TNE 320, TNE 400, TNE 410 TNE 420, TNE 430, TNE 500, TNE 510, TNE 520, TNE 600, TNE 620, TNE 700, TNE 720, NE 100, NE 120, NE 200, NE 210, NE 220, NE 230, NE 300, NE 310, NE 320, NE 400, NE 410 NE 420, NE 430, NE 500, NE 510, NE 520, NE 600, NE 620, NE 700, NE 720, ANE 200, ANE 230, AND 400, and ANE 430 commercially available from Osram Sylvania. Suitable unencapsulated electroluminescent phosphors include 723 EL, 727 EL, 728 EL, 729 EL, 813 EL, and 814 EL commercially available from Osram Sylvania. These materials may emit red, green, yellow, blue or orange colored light based upon the particular phosphor employed. The preferred electroluminescent phosphors are TNE 100, TNE 200, TNE 410, and TNE 700, commercially available from Osram Sylvania.

The photocurable mixture of the electroluminescent composition includes at least one oligomer. The at least one oligomer is preferably present in an amount of about 10% to 40% of the weight of the electroluminescent composition. In a particularly preferred embodiment the at least one oligomer is present in an amount of about 34% of the weight of the electroluminescent composition. In another particularly preferred embodiment the at least one oligomer is present in an amount of about 12% of the weight of the electroluminescent composition. Preferably, the at least one oligomer is selected from the group consisting of an acrylated urethane oligomer, an acrylic oligomer, an epoxy oligomer, a polyester oligomer, and mixtures thereof. More preferably, the at least one oligomer includes an aliphatic acrylated oligomer. Most preferably, the at least one oligomer is a urethane oligomer. Suitable aliphatic acrylated oligomers include Radcure Ebecryl 244 aliphatic urethane diacrylate diluted 10% with 1,6-hexanediol diacrylate),

Ebecryl 264 (aliphatic urethane triacrylate diluted 15% with 1,6-hexanediol diacrylate), Ebecryl 284 (aliphatic urethane diacrylate diluted 10% with 1, 6-hexanediol diacrylate) commercially available from Radcure UCB Corp. of Smyrna, Georgia; Sartomer CN-961E75 (aliphatic urethane diacrylate blended with 25%
5 ethoxylated trimethylol propane triacrylate), CN-961H81 (aliphatic urethane diacrylate blended with 19% 2(2-ethoxyethoxy)ethyl acrylate), CN-963A80 (aliphatic urethane diacrylate blended with 20% tripropylene glycol diacrylate), CN-964 (aliphatic urethane diacrylate), CN-966A80 (aliphatic urethane diacrylate blended with 20% tripropylene glycol diacrylate), CN-982A75 (aliphatic urethane
10 diacrylate blended with 25% tripropylene glycol diacrylate) and CN-983 (aliphatic urethane diacrylate), commercially available from Sartomer Corp. of Exton, Pennsylvania; TAB FAIRAD 8010, 8179, 8205, 8210, 8216, 8264, M-E-15, UVU-316, commercially available from TAB Chemicals of Chicago, Illinois; and Echo Resin ALU-303, commercially available from Echo Resins of Versaille, Missouri;
15 and Genomer 4652, commercially available from Rahn Radiation Curing of Aurora, IL. The preferred aliphatic acrylated oligomers include Ebecryl 264 and Ebecryl 284. Ebecryl 264 is an aliphatic urethane triacrylate of 1200 molecular weight supplied as an 85% solution in hexanediol diacrylate. Ebecryl 284 is aliphatic urethane diacrylate of 1200 molecular weight diluted 10% with 1,6-hexanediol
20 diacrylate. Combinations of these materials may also be employed herein.

The photocurable composition of the electroluminescent composition also includes an acrylated monomer which is preferably an isobornyl acrylate. Preferably, the isobornyl acrylate monomer is present in an amount of about 4% to 30% of the electroluminescent composition. In one particularly preferred
25 embodiment of the present invention, the isobornyl acrylate monomer is present in an amount of about 20% of the electroluminescent composition. In another particularly preferred embodiment of the present invention, the isobornyl acrylate monomer is present in an amount of about 8% of the electroluminescent composition. Suitable isobornyl acrylate monomers include Sartomer SR423

(isobornyl methacrylate) and SR506 (isobornyl acrylate) available from Sartomer Corp.; Radcure IBOA (isobornyl acrylate), commercially available from Radcure Corp.; IBOA and IBOMA, commercially available from CPS Chemical of Bradford, England; and Genomer 1121, commercially available from Rahn Radiation Curing.

- 5 The preferred isobornyl acrylate monomer is Radcure IBOA, commercially available from Radcure Corp. Radcure IBOA is a high purity, low color monomer. Combinations of these materials may also be employed herein.

10 The preferred photocurable composition of the electroluminescent composition optionally includes an adhesion promoter preferably in an amount of about 1% to 10% the electroluminescent composition. In one particularly preferred embodiment of the present invention the adhesion promoter is present in an amount of about 7%. In another particularly preferred embodiment of the present invention the adhesion promoter is present in an amount of about 3% of the electroluminescent composition. Suitable adhesion promoters include Ebecryl 168 and Ebecryl 170, commercially available from Radcure Corp.; and Sartomer CN 15 704 (acrylated polyester adhesion promoter) and CD 9052 (trifunctional acid ester), commercially available from Sartomer Corp. The preferred adhesion promoter is Ebecryl 168 which is a methacrylated acidic adhesion promoter. Combinations of these materials may also be employed herein.

20 The preferred photocurable composition of the electroluminescent composition optionally includes a flow promoting agent preferably in an amount of about 0.1% to 5% of the electroluminescent composition. In one particularly preferred embodiment of the present invention the flow promoting agent is present in an amount of about 3%. In another particularly preferred embodiment of the present invention the flow promoting agent is present in an amount of about 1% of 25 the electroluminescent composition. Suitable flow promoting agents include Genorad 17, commercially available from Rahn Radiation Curing; and Modaflow, commercially available from Monsanto Chemical Co., St. Louis, Missouri. The

preferred flow promoting agent is Modaflow which is an ethyl acrylate and 2-ethylhexyl acrylate copolymer that improves the flow of the composition. Combinations of these materials may also be employed herein.

The photoinitiator of the electroluminescent composition is preferably in an amount of about 0.5% to 6% of the electroluminescent composition. In one particularly preferred embodiment of the present invention the photoinitiator is present in an amount of about 3%. In another particularly preferred embodiment of the present invention the photoinitiator is present in an amount of about 1% of the electroluminescent composition. Suitable photoinitiators include Iragure 1800, Iragure 1850, Irgacure 184 (1-hydroxycyclohexyl phenyl ketone), Irgacure 907 (2-methyl-1-[4-(methylthio)phenyl]-2-morpholino propan-1-one), Irgacure 369 (2-benzyl-2-N,N-dimethylamino-1-(4-morpholinophenyl)-1-butanone), Irgacure 500 (the combination of 50% 1-hydroxy cyclohexyl phenyl ketone and 50% benzophenone), Irgacure 651 (2,2-dimethoxy-1,2-diphenylethan-1-one), Irgacure 1700 (the combination of 25% bis(2,6-dimethoxybenzoyl-2,4,4-trimethyl pentyl) phosphine oxide and 75% 2-hydroxy-2-methyl-1-phenyl-propan-1-one), and DAROCUR 1173 (2-hydroxy-2-methyl-1-phenyl-1-propane), and DAROCUR 4265 (the combination of 50% 2,4,6-trimethylbenzoyldiphenyl-phosphine oxide and 50% 2-hydroxy 2-methyl-1-phenyl-propan-1-one), commercially available from Ciba-Geigy Corp., Tarrytown, N.Y.; CYRACURE UVI-6974 (mixed triaryl sulfonium hexafluoroantimonate salts) and cyracure UVI-6990 (mixed triaryl sulfonium hexafluorophosphate salts) available commercially from Union Carbide Chemicals and Plastics Co. Inc., Danbury, Connecticut; and Genocure CQ, Genocure BDK, and Genocure M.F., commercially available from Rahn Radiation Curing. The preferred photoinitiator is Irgacure 1700 commercially available from Ciba-Geigy of Tarrytown, New York. Combinations of these materials may also be employed herein.

To illustrate, the following example sets forth a presently preferred electroluminescent composition according to this aspect of the invention.

UV curable electroluminescent Composition 1

5 This example provides an electroluminescent composition that is used to form the electroluminescent active layer. The electroluminescent composition was made from the following components:

Component	Approximate Weight %
Ebecryl 264	16.7
Ebecryl 284	16.7
IBOA	20.0
Ebecryl 168	6.7
Modaflow	3.3
Irgacure 1700	3.3
TNE 200	33.3
Total	100.00

10 In this example the IBOA and Irgacure 1700 are mixed in a pan with a propeller blade mixer for 30 seconds at a speed of 500 to 1000 rpm. In the next step, the Ebecryl 264, the Ebecryl 284, and the Modaflow are introduced into the pan and mixed for 1 to 2 minutes at a speed of 2000 rpm. In the final step, the
 20 Ebecryl 168 adhesion promoter and TNE 200 phosphor are introduced into the pan and are mixed for 1 to 2 minutes at a speed of 2000 rpm. The temperature during mixing is monitored. The mixing is temporarily suspended if the temperature exceed 100°F. This particular electroluminescent composition may be used by the method below to produce an active layer that emits bluish-green light.

UV curable electroluminescent Composition 2

This example provides an electroluminescent composition that is used to form the electroluminescent active layer. The electroluminescent composition was made from the following components:

Component	Approximate Weight %
Ebecryl 264	6.3
Ebecryl 284	6.3
IBOA	7.5
Ebecryl 168	2.5
Modaflow	1.3
Irgacure 1700	1.3
ANE 430	49.8
813 EL	25.0
Total	100.00

In this example the IBOA and Irgacure 1700 are mixed in a pan with a propeller blade mixer for 30 seconds at a speed of 500 to 1000 rpm. In the next step, the Ebecryl 264, the Ebecryl 284, and the Modaflow are introduced into the pan and mixed for 1 to 2 minutes at a speed of 2000 rpm. In the final step, the Ebecryl 168 adhesion promoter, ANE 430 phosphor, and 813 EL phosphor are introduced into the pan and are mixed for 1 to 2 minutes at a speed of 2000 rpm. The temperature during mixing is monitored. The mixing is temporarily suspended if the temperature exceed 100°F. This particular electroluminescent composition may be used by the method below to produce an active layer that emits bluish-green light.

Compositions for forming the Opaque Conductive Layers

In a preferred embodiment of the present invention, the opaque conductive layer is made from a silver composition. The silver composition preferably comprises a photocurable mixture, a silver metal containing mixture, a photoinitiator.

The photocurable mixture of the silver composition preferably comprises an aliphatic acrylated oligomer. The aliphatic acrylated oligomer is present in an amount of about 3% to 8%, and preferably about 8%, of the silver composition. The aliphatic acrylated oligomer preferably comprises a urethane oligomer. Suitable aliphatic acrylated oligomers include the same oligomers enumerated above for the photocurable mixture of the electroluminescent composition.

The photocurable mixture of the silver composition further includes an acrylated epoxy oligomer. The acrylated epoxy oligomer is present in an amount of about 2% to 4%, and preferably about 3%, of the silver composition. Suitable acrylated epoxy oligomers include Radcure Ebecryl 3603, commercially available from Radcure UCB Corp.; Sartomer CN120 and CN124, commercially available from Sartomer Corp.; and Echo Resin TME 9310 and 9345, commercially available from Echo Resins. The preferred acrylated epoxy oligomer is Ebecryl 3603, which tri-functional acrylated epoxy novolac. Combinations of these materials may also be employed herein.

The photocurable mixture of the silver composition preferably further includes an isobornyl acrylate monomer in an amount of about 4% to 8%, and preferably about 5%, of the silver composition. Suitable isobornyl acrylate monomers include the monomer enumerated above for the electroluminescent composition.

The photocurable mixture of the silver composition preferably further includes a flow promoting agent in an amount of about 0.1% to 2%, and preferably about 1.0%, of the silver composition. Suitable flow promoting agents include the same agents enumerated above for the electroluminescent composition.

- 5 The silver mixture of the silver composition preferably includes a silver powder in an amount of about 50% to 60%, and preferably about 52%, of the silver composition. The silver powder comprises a plurality of particles. In this preferred silver composition, the silver powder has a particle size range for these particles of about 5 microns to about 15 microns. In some embodiments, the silver powder has a particle size range of about 4.7 microns to about 14.9 microns. Preferably, the silver powder particles have a particle size distribution wherein about 10% of the particles have a particle size of less than about 4.7 microns, about 50% of the particles have a particle size of less than about 7.6 microns, and about 90% of the particles have a particle size of less than about 14.9 microns. The preferred silver powders are Silver Powder EG-ED and Silver Powder C-ED commercially available from Degussa Corp. of South Plainfield, New Jersey.
- 10
- 15

- The silver powder according to the presently-preferred composition comprises EGED, commercially available from Degussa Corp. of South Plainfield, New Jersey. Such silver also may be obtained from other commercial sources, e.g., such as Englehard Chemical Co. of Iselin, New Jersey. The presently preferred silver powder has a grain size distribution ranging from about 5 microns to about 15 microns. This presently preferred silver powder has a particle size distribution as follows:
- 20

TABLE 1. Silver Powder Particle Size Distribution

	<u>Size Range (microns)</u>	<u>Percentage</u>
5	< 4.7	10%
	< 7.6	50%
	< 14.9	90%

As this table indicates, within a sample of the silver powder, 10% of the grains have a size of less than 4.7 microns, 50% of the grains have a particle size of less than 7.6 microns, and 90% of the grains have a particle size of less than 14.9 microns.

10 The silver mixture of the silver composition preferably further includes a silver flake composition in an amount of about 25% to 35%, and preferably about 30%, of the silver composition. The silver flake composition comprises a plurality of flakes which comprise, and which preferably consist essentially of, silver. The silver flake composition according to this embodiment has

15 a particle size range of about 5 microns to about 32 microns. More preferably, the silver flake composition has a particle size range of about 5.5 microns to about 32.0 microns. The silver flake particle size distribution preferably is such that about 10% of the particles have a particle size of less than about 5.5 microns, about 50% of the particles have a particle size of less than about 12.5 microns, and about 90% of the

20 particles have a particle size of less than about 32.0 microns. The preferred silver flake compositions are Silver Flake # 25, Silver Flake #1, and Silver Flake #7A commercially available from Degussa Corp. of South Plainfield, New Jersey.

25 The silver flake according to the presently-preferred composition of Example I comprises SF25, commercially available from Degussa. This silver flake composition preferably has a grain size distribution ranging from about 5 microns to about 32 microns. It has a particle size distribution as follows:

TABLE 2. Silver Flake Composition Particle Size Distribution

	<u>Size Range (microns)</u>	<u>Percentage</u>
	< 5.5	10%
	< 12.5	50%
5	< 32.0	90%

As indicated in Table 2, within a sample of the silver flake, 10% of the flakes have a size of less than 5.5 microns, 50% of the flakes have a particle size of less than 12.5 microns, and 90% of the flakes have a particle size of less than 32.0 microns.

10 The photoinitiator of the silver composition is preferably present in an amount of about 3% to 6%, and preferably about 4%, of the silver composition. Suitable photoinitiators include the same photoinitiators enumerated above for the electroluminescent compositions.

UV curable opaque conductive composition 3

15 This example provides a silver composition that is used to form the opaque conductive layer. The silver composition is made from the following components:

	<u>Component</u>	<u>Approximate Weight</u> <u>%</u>
	Ebecryl 264	7.2
20	Ebecryl 3603	2.4
	IBOA	4.7
	Silver Powder EGED	53.4
	Silver Flake # 25	27.6
	Iragure 1700	3.9
25	Modaflow	0.8
	Total	100.00

In this example the IBOA and Iragure 1700 are mixed in a pan with a propeller blade mixer for 30 seconds at a speed of 500 to 1000 rpm. Next, the Ebecryl 264, the Ebecryl 3603, and the Modaflow are introduced into the pan and mixed for 1 to 2 minutes at a speed of 1000 rpm. In the next step, the EGED silver powder, and the Silver Flake #25 are introduced into the pan and are mixed for 1 to 2 minutes at a speed of 1000 rpm. Finally, the mixing speed is increased to 10,000 rpm and mixed for an additional 5 minutes.

For best results, the silver powder is washed prior to addition to the mixture. The washing process includes a first step of loading the powder in a sealable container. A mixture consisting of 17% methyl ethyl ketone and 83% silver composition is added to the container and the slurry is mixed with a propeller blade for 5 minutes at 500 rpm. The methyl ethyl ketone is poured off and the silver powder is allowed to air dry. During the drying stage the powder is periodically mixed.

UV curable opaque conductive composition 4

This example provides a silver composition that is used to form the opaque conductive layer. The silver composition is made from the following components:

Component	Approximate Weight %
Ebecryl 264	4.2
Ebecryl 3603	2.7
IBOA	7.7
Silver Powder EGED	53.4
Silver Flake #25	27.6
Iragure 1700	3.8
Modaflow	0.6
Total	100.00

In this example the IBOA and Iragure 1700 are mixed in a pan with a propeller blade mixer for 30 seconds at a speed of 500 to 1000 rpm. Next, the Ebecryl 264, the Ebecryl 3603, and the Modaflow are introduced into the pan and mixed for 1 to 2 minutes at a speed of 1000 rpm. In the next step, the EGED silver powder, and the Silver Flake #25 are introduced into the pan and are mixed for 1 to 2 minutes at a speed of 1000 rpm. Finally, the mixing speed is increased to 10,000 rpm and mixed for an additional 5 minutes.

UV curable opaque conductive composition 5

This example provides a silver composition that is used to form the opaque conductive layer. The silver composition is made from the following components:

Component	Approximate Weight %
Ebecryl 264	7.0
Ebecryl 3603	2.3
IBOA	4.6
Silver Powder EGED	52.3
Silver Flake # 25	27.0
Iragure 1700	3.8
Modaflow	0.8
Ebecryl 168	2.2
Total	100.00

In this example the IBOA and Iragure 1700 are mixed in a pan with a propeller blade mixer for 30 seconds at a speed of 500 to 1000 rpm. Next, the Ebecryl 264, the Ebecryl 3603, and the Modaflow are introduced into the pan and mixed for 1 to 2 minutes at a speed of 1000 rpm. In the next step, the EGED silver powder, and the Silver Flake #25 are introduced into the pan and are mixed for 1 to 2 minutes at a speed of 1000 rpm. In the next step, the Ebecryl 168 is added into the pan and the combination mixed at 1000 rpm for 1 to 2 minutes. Finally, the mixing speed is increased to 10,000 rpm and mixed for an additional 5 minutes.

This example contains Ebecryl 168 added as an adhesion promoter. This material is a methacrylate ester derivative commercially available from Radcure UCB Corp. of Smyrna, Georgia.

Compositions for forming the transparent conductive layer

5 In a preferred embodiment of the present invention, the transparent conductive layer is made from a transparent conductive composition. In this preferred embodiment, the transparent conductive composition comprises a photocurable mixture, a conductive powder, and a photoinitiator.

10 The photocurable mixture of the transparent conductive composition preferably includes a mixture of aliphatic acrylated oligomers. The aliphatic acrylated oligomer mixture is present in an amount of about 10% to 40% of the transparent conductive composition. The aliphatic acrylated oligomer mixture is more preferably present in an amount of about 20% to 30%, and most preferably about 27%. The aliphatic acrylated oligomer preferably comprises one or more
15 urethane oligomers. Suitable aliphatic acrylated oligomers include the same oligomers listed above for the electroluminescent composition.

 The photocurable mixture of the transparent conductive composition preferably includes an acrylated epoxy oligomer. The acrylated epoxy oligomer is present in an amount of about 3% to 11%. The acrylated epoxy oligomer is more
20 preferably present in an amount of about 5% to 9%, and most preferably about 7%. Suitable acrylated epoxy oligomers include the same oligomers listed above for the silver composition.

 The photocurable mixture of the transparent conductive composition preferably includes an isobornyl acrylate monomer in an amount of about 10% to
25 40%. The isobornyl acrylate monomer is more preferably present in an amount of

about 20% to 35%, and most preferably about 28%. Suitable isobornyl acrylate monomers include the same monomers listed above for the electroluminescent composition.

5 The photocurable mixture of the transparent conductive composition optionally includes a flow promoting agent in an amount of about 0.1% to 8%. The flow promoting agent is more preferably present in an amount of about 3% to 5%, and most preferably about 3.5%. Suitable flow promoting agents include the same agents listed above for the electroluminescent compositions.

10 The conductive powder of the present invention is preferably present in an amount of about 20% to 50%. The conductive powder is more preferably present in an amount of about 30% to 40%, and most preferably about 33%. Preferred conductive powders include metal powders, metal oxide powders, and metal nitride powders. Suitable conductive powders include silver powder, tin oxide powder, and indium tin oxide powder. Minatec 30, and Minatec 40. The
15 preferred conductive powders are Minatec 30 and Minatec 40 commercially available from EM Industries located in Hawthorne, New York.

This photoinitiator of the transparent conductive composition is preferably present in an amount of about 2% to 10% of the transparent conductive composition. The photoinitiator is more preferably present in an amount of about
20 4% to 6%, and most preferably about 5%. Suitable photoinitiators include the same photoinitiators enumerated above for the electroluminescent composition.

UV curable transparent conductive composition 6

This example provides a transparent conductive composition that is used to form the transparent conductive layer. The transparent conductive
25 composition is made from the following components:

Component	Approximate Weight %
Ebecryl 264	26.7
IBOA	28.3
Irgacure 1700	5.0
Ebecryl 3603	6.6
Modaflow	3.5
Minatec 30	33.4
Total	100.00

5

10 In this example the IBOA and Irgacure 1700 are mixed in a pan with a propeller blade mixer for 30 seconds at a speed of 500 to 1000 rpm. In the next step, the Ebecryl 264, the Ebecryl 3603, and Modaflow are introduced into the pan and mixed for 1 to 2 minutes at a speed of 2000 rpm. In the final step, the Minatec 30 is added and mixed at 2000 rpm for 1 to 2 minutes. The mixing is temporarily suspended if the temperature exceed 100°F.

15

UV curable transparent conductive composition 7

This example provides a transparent conductive composition that is used to form the transparent conductive layer. The transparent conductive composition is made from the following components:

20

Component	Approximate Weight %
Ebecryl 264	26.7
IBOA	28.3
Irgacure 1700	5.0
Ebecryl 3603	6.6
Modaflow	3.5
Minatec 40	33.4
Total	100.00

25

In this example the IBOA and Irgacure 1700 are mixed in a pan with a propeller blade mixer for 30 seconds at a speed of 500 to 1000 rpm. In the next step, the Ebecryl 264, the Ebecryl 3603, and Modaflow are introduced into the pan and mixed for 1 to 2 minutes at a speed of 2000 rpm. In the final step, the Minattec
 5 40 is added and mixed at 2000 rpm for 1 to 2 minutes. The mixing is temporarily suspended if the temperature exceed 100°F.

Compositions for forming the dielectric layer

In accordance with one aspect of the invention, a presently preferred ultraviolet light (UV) curable dielectric composition ("dielectric composition") is
 10 provided. In this preferred embodiment, the UV curable dielectric composition includes a photocurable mixture, a photoinitiator, and dielectric material.

The photocurable mixture of the UV curable dielectric mixture includes at least one oligomer. The at least one oligomer is present in an amount of about 10% to 40% of the dielectric composition. The at least one oligomer is more
 15 preferably present in an amount of about 14% to 30% of the dielectric composition, and most preferably about 20% of the dielectric composition. Preferably, the at least one oligomer is selected from the group consisting of an acrylated urethane oligomer, an acrylic oligomer, an epoxy oligomer, a polyester oligomer, and mixtures thereof. More preferably, the at least one oligomer is an aliphatic
 20 acrylated oligomer. Most preferably, the at least one oligomer is a urethane oligomer. Suitable aliphatic acrylated oligomers include Radcure Ebecryl 244, Ebecryl 264 and Ebecryl 284 urethanes, commercially available from Radcure UCB Corp. of Smyrna, Georgia; Sartomer CN961, CN963, CN964, CN 966, CN982 and CN 983, commercially available from Sartomer Corp. of Exton, Pennsylvania; TAB
 25 FAIRAD 8010, 8179, 8205, 8210, 8216, 8264, M-E-15, UVU-316, commercially available from TAB Chemicals of Chicago, Illinois; and Echo Resin ALU-303, commercially available from Echo Resins of Versailles, Missouri; and Genomer

4652, commercially available from Rahn Radiation Curing of Aurora, IL. The preferred aliphatic acrylated oligomers include Ebecryl 264 and Ebecryl 284. Ebecryl 264 is an aliphatic urethane triacrylate supplied as an 85% solution in hexandiol diacrylate. Ebecryl 284 is aliphatic urethane diacrylate of 1200 molecular weight diluted with 1,6-hexanediol diacrylate. Combinations of these materials may also be employed herein.

The photocurable mixture of the UV curable dielectric mixture also includes an isobornyl acrylate monomer in an amount of about 5% to 30% of the dielectric composition. The isobornyl acrylate monomer is more preferably present in an amount of about 8% to 16% of the dielectric composition, and most preferably about 12% of the dielectric composition. Suitable isobornyl acrylate monomers include Sartomer SR423 IBOMA and SR506 IBOA; Radcure IBOA, commercially available from Radcure Corp.; IBOA and IBOMA, commercially available from CPS Chemical; and Genomer 1121, commercially available from Rahn Radiation Curing. The preferred isobornyl acrylate monomers is Radcure IBOA, commercially available from Radcure Corp. Combinations of these materials may also be employed herein.

The photocurable mixture of the UV curable dielectric mixture optionally includes an adhesion promoter in an amount of about 1% to 10% of the dielectric composition. The adhesion promoter is more preferably present in an amount of about 1% to 5% of the dielectric composition, and most preferably about 4% of the dielectric composition. Suitable adhesion promoters include Ebecryl 168, commercially available from Radcure Corp.; and Sartomer CN 704 and CD 9052, commercially available from Sartomer Corp. The preferred adhesion promoter is Ebecryl 168 which is a methacrylated acidic adhesion promoter. Combinations of these materials may also be employed herein.

The photocurable mixture of the UV curable dielectric mixture optionally includes a flow promoting agent in an amount of about 0.1% to 6% of the dielectric composition. The flow promoting agent is more preferably present in an amount of about 1 to 3% of the dielectric composition, and most preferably about 2% of the dielectric composition. Suitable flow promoting agents include Genorad 17, commercially available from Rahn Radiation Curing; and Modaflow, commercially available from Monsanto Chemical Co., St. Louis, Missouri. The preferred flow promoting agent is Modaflow which is an ethyl acrylate and 2-ethylhexyl acrylate copolymer that improves the flow of the composition. Combinations of these materials may also be employed herein.

This preferred dielectric composition also includes a photoinitiator in an amount of about 0.5% to 10% of the dielectric composition. The photoinitiator is more preferably present in an amount of about 2% to 6% of the dielectric composition, and most preferably about 4% of the dielectric composition. Suitable photoinitiators include Iragure 819XF, Irgacure 184 (1-hydroxycyclohexyl phenyl ketone), Irgacure 907 (2-methyl-1-[4-(methylthio)phenyl]-2-morpholino propan-1-one), Irgacure 369 (2-benzyl-2-N,N-dimethylamino-1-(4-morpholinophenyl)-1-butanone), Irgacure 500 (the combination of 1-hydroxy cyclohexyl phenyl ketone and benzophenone), 651 (2,2-dimethoxy-2-phenyl acetophenone), Irgacure 1700 (the combination of bis(2,6-dimethoxybenzoyl-2,4,4-trimethyl pentyl) phosphine oxide and 2-hydroxy-2-methyl-1-phenyl-propan-1-one), Ciba-Geigy 1700, and DAROCUR 1173 (2-hydroxy-2-methyl-1-phenyl-1-propane) and 4265 (the combination of 2,4,6-trimethylbenzoyldiphenyl-phosphine oxide and 2-hydroxy 2-methyl-1-phenyl-propan-1-one), available commercially from Ciba-Geigy Corp., Tarrytown, N.Y.; CYRACURE UVI-6974 (mixed triaryl sulfonium hexafluoroantimonate salts) and UVI-6990 (mixed triaryl sulfonium hexafluorophosphate salts) available commercially from Union Carbide Chemicals and Plastics Co. Inc., Danbury, Conn.; and Genocure CQ, Genocure BDK, and Genocure M.F., commercially available from Rahn Radiation Curing. The

preferred photoinitiators are Irgacure 1700, Iragure 819XF, and Darocur 1173 commercially available from Ciba-Geigy of Tarrytown, New York. Combinations of these materials may also be employed herein.

5 The preferred dielectric composition also includes dielectric material in an amount of about 30% to 80% of the dielectric composition. The dielectric material is more preferably present in an amount of about 40% to 70% of the dielectric composition, and most preferably about 60% of the dielectric composition. Preferably, the dielectric material is an oxide or a mixture of oxides which have a high dielectric constant and high resistivities. Preferred dielectric includes barium
10 titanate (available from GFS Chemical Co.), titanium dioxide (Tint-AYD), zirconium oxide, and the like. Combinations of these materials may also be employed herein.

To illustrate, the following example sets forth a presently preferred dielectric composition according to this aspect of the invention.

15 **UV curable dielectric composition 8**

This example provides a preferred dielectric composition according to the invention that can be used for applying a dielectric layer preferably by screen printing techniques. Suitable substrates include glass, metals, and polycarbonate. These substrates are preferably precoated with one or more layers of an
20 electroluminescent lamp. The dielectric composition was made from the following components:

Component	Approximate Weight %
Ebecryl 264	9.8
Ebecryl 284	9.8
IBOA	11.8
Ebecryl 168	3.8
Modaflow	2.0
Irgacure 1700	3.0
Darocur 1173	0.8
Iragure 819XF	0.2
White preblend - mixture of PC 9003 and IBOA	24.5
Barium Titanate	34.3
Total	100.00

In this example, the first step is to prepare the white preblend. The white preblend is a mixture of titanium oxide and IBOA in a weight ratio of 61.5/38.5. PC9003 and the IBOA are mixed in a 61.5/38.5 weight ratio and mixed stirred until smooth to form a first mixture. Mixing is typically accomplished by stirring at 1000-1500 rpm for approximately 5 minutes and then at 2500-3000 for an additional 15 to 20 minutes. The next step is to mix the Iragure 819XF powder into the liquid Darocur 1173 at about 120 °F while stirring at 500-1000 rpm to form a second mixture. Stirring in this second step lasted for about 30 seconds. Next the first and second mixtures are combined and then stirred to form a third mixture. Next, the Ebecryl 264, the Ebecryl 284, the modaflow and the white preblend are added to the third mixture to form a fourth mixture. The fourth mixture is stirred until uniform. Next the barium titanate is added and stirred until uniform to form a sixth mixture. The Ebecryl 168 is then added to the sixth mixture to form the UV curable dielectric.

Clear-coat Compositions

In a preferred embodiment of the present invention, the clear-coat layer is made from a UV curable clear-coat composition. In this preferred embodiment, the clear-coat composition comprises a photocurable mixture and a photoinitiator.

The photocurable mixture of the clear-coat composition includes a at least one aliphatic acrylated oligomer. Preferably, the at least one aliphatic acrylated oligomer is present in an amount of about 10% to 40% of the clear-coat composition. The aliphatic acrylated oligomer mixture is more preferably present in an amount of about 20% to 30% of the clear-coat composition, and most preferably about 24% of the clear-coat composition. The aliphatic acrylated oligomer preferably comprises one or more urethane oligomers. Suitable aliphatic acrylated oligomers include Radcure Ebecryl 244, Ebecryl 264 and Ebecryl 284 urethanes, commercially available from Radcure UCB Corp. of Smyrna, Georgia; Sartomer CN961, CN963, CN964, CN 966, CN982 and CN 983, commercially available from Sartomer Corp. of Exton, Pennsylvania; TAB FAIRAD 8010, 8179, 8205, 8210, 8216, 8264, M-E-15, UVU-316, commercially available from TAB Chemicals of Chicago, Illinois; and Echo Resin ALU-303, commercially available from Echo Resins of Versaille, Missouri; and Genomer 4652, commercially available from Rahn Radiation Curing of Aurora, IL. The preferred aliphatic acrylated oligomers include Ebecryl 264 and Ebecryl 284. Ebecryl 264 is an aliphatic urethane triacrylate supplied as an 85% solution in hexandiol diacrylate. Ebecryl 284 is aliphatic urethane diacrylate of 1200 molecular weight diluted with 1,6-hexanediol diacrylate. Combinations of these materials may also be employed herein.

The photocurable mixture of the clear-coat composition includes an acrylated epoxy oligomer. The acrylated epoxy oligomer is present in an amount of

about 5% to 20% of the clear-coat composition. The acrylated epoxy oligomer is more preferably present in an amount of about 8% to 16% of the clear-coat composition, and most preferably about 12% of the clear-coat composition. Suitable acrylated epoxy oligomers include Radcure Ebecryl 3603, commercially available from Radcure UCB Corp.; Sartomer CN120 and CN124, commercially available from Sartomer Corp.; and Echo Resin TME 9310 and 9345, commercially available from Echo Resins. The preferred acrylated epoxy oligomer is Ebecryl 3603, which tri-functional acrylated epoxy novolac. Combinations of these materials may also be employed herein.

10 The photocurable mixture of the clear-coat composition also includes an isobornyl acrylate monomer in an amount of about 40% to 60% of the clear-coat composition. The isobornyl acrylate monomer is more preferably present in an amount of about 45% to 55% of the clear-coat composition, and most preferably about 52% of the clear-coat composition. Suitable isobornyl acrylate monomers include Sartomer SR423 IBOMA and SR506 IBOA; Radcure IBOA, commercially available from Radcure Corp.; IBOA and IBOMA, commercially available from CPS Chemical; and Genomer 1121, commercially available from Rahn Radiation Curing. The preferred isobornyl acrylate monomers is Radcure IBOA, commercially available from Radcure Corp. Combinations of these materials may also be employed herein.

25 The photocurable mixture of the clear-coat composition optionally includes a flow promoting agent in an amount of about 0.1% to 8%, and preferably about 4.5%, of the clear-coat composition. Suitable flow promoting agents include Genorad 17, commercially available from Rahn Radiation Curing; and Modaflow, commercially available from Monsanto Chemical Co., St. Louis, Missouri. The preferred flow promoting agent is Modaflow which is an ethyl acrylate and 2-ethylhexyl acrylate copolymer that improves the flow of the composition. Combinations of these materials may also be employed herein.

This preferred clear-coat composition also includes a photoinitiator in an amount of about 4% to 12% of the clear-coat composition. The photoinitiator is more preferably present in an amount of about 6% to 10%, and most preferably about 8%. Suitable photoinitiators include Irgacure 184 (1-hydroxycyclohexyl phenyl ketone), Irgacure 907 (2-methyl-1-[4-(methylthio)phenyl]-2-morpholino propan-1-one), Irgacure 369 (2-benzyl-2-N,N-dimethylamino-1-(4-morpholinophenyl)-1-butanone), Irgacure 500 (the combination of 1-hydroxy cyclohexyl phenyl ketone and benzophenone), 651 (2,2-dimethoxy-2-phenyl acetophenone), Irgacure 1700 (the combination of bis(2,6-dimethoxybenzoyl-2,4,4-trimethyl pentyl phosphine oxide and 2-hydroxy-2-methyl-1-phenyl-propan-1-one), Ciba-Geigy 1700, and DAROCUR 1173 (2-hydroxy-2-methyl-1-phenyl-1-propane) and 4265 (the combination of 2,4,6-trimethylbenzoyldiphenyl-phosphine oxide and 2-hydroxy 2-methyl-1-phenyl-propan-1-one), available commercially from Ciba-Geigy Corp., Tarrytown, N.Y.; CYRACURE UVI-6974 (mixed triaryl sulfonium hexafluoroantimonate salts) and UVI-6990 (mixed triaryl sulfonium hexafluorophosphate salts) available commercially from Union Carbide Chemicals and Plastics Co. Inc., Danbury, Conn.; and Genocure CQ, Genocure BDK, and Genocure M.F., commercially available from Rahn Radiation Curing. The preferred photoinitiator is Irgacure 1700 commercially available from Ciba-Geigy of Tarrytown, New York. Combinations of these materials may also be employed herein.

To illustrate, the following example sets forth a presently preferred clear-coat composition according to this aspect of the invention.

UV curable clear-coat composition 9

This example provides a clear-coat composition that is used to form the transparent conductive layer. The clear-coat composition is made from the following components:

Component	Approximate Weight %
Ebecryl 264	12.0
Ebecryl 284	12.0
IBOA	51.5
Irgacure 1700	8.0
Ebecryl 3603	12.0
Modaflow	4.5
Total	100.00

5

10 In this example the IBOA and Irgacure 1700 are mixed in a pan with a propeller blade mixer for 30 seconds at a speed of 500 to 1000 rpm. In the next step, the Ebecryl 264, the Ebecryl 284, the Ebecryl 3603, and Modaflow are introduced into the pan and mixed for 1 to 2 minutes at a speed of 2000 rpm. The mixing is temporarily suspended if the temperature exceed 100°F.

Examples of the Methods of Preparing Electroluminescent Lamps

15

Example 1

UV curable opaque conductive composition 3 described above is applied by screen printing to a plastic sheet substrate. The composition is irradiated with a UV gallium-doped metal halide lamp (curing energy approximately 350 mJ/cm²) lamp for approximately 2 seconds to form an opaque conductive layer on the plastic sheet which is approximately 0.5 mil thick. UV curable electroluminescent composition 1 described above is next screen printed on the conductive layer. The electroluminescent composition is next irradiated with the same lamp for approximately 2 seconds to form an electroluminescent active layer which is approximately 1.5 mil thick. UV curable dielectric composition 8 described above is next screen printed on the electroluminescent layer. The dielectric composition is irradiated with the same UV lamp for approximately 2 seconds to form a dielectric layer which is approximately 0.3 mil thick. The dielectric layer is next over-coated by screen printing with UV curable transparent

conductive composition 6 described above. The transparent conductive composition is next irradiated with the same UV lamp to form the transparent conductive layer which is approximately 0.8 mil thick. Finally, the electroluminescent lamp is completed by screen printing the clear-coat composition 9 onto the transparent
5 conductive layer. The clear-coat is then irradiated with the same UV lamp to form the outer protective clear-coat layer which is approximately 0.5 mil thick.

Example 2

UV curable transparent conductive composition 6 described above is applied by screen printing to a plastic sheet substrate. The transparent conductive
10 composition is irradiated with a UV gallium-doped metal halide lamp (curing energy approximately 350 mJ/cm^2) for approximately 2 seconds to form a transparent conductive layer which is approximately 0.8 mil thick on the plastic sheet. UV curable electroluminescent composition 1 described above is next screen printed on the conductive layer. The electroluminescent composition is next
15 irradiated with the same lamp for approximately 2 seconds to form an electroluminescent active layer which is approximately 1.5 mil thick. UV curable dielectric composition 8 described above is next screen printed on the electroluminescent layer. The dielectric composition is irradiated with the same UV lamp for approximately 2 seconds to form a dielectric layer which is approximately
20 0.8 mil thick. The dielectric layer is next over-loaded by screen printing with UV curable opaque conductive composition 3 described above. The opaque conductive composition is next irradiated with the same UV lamp to form the opaque conductive layer which is approximately 0.5 mil thick. Finally, the electroluminescent lamp is completed by screen printing the clear-coat composition
25 9 onto the conductive layer. The clear-coat is then irradiated with the same UV lamp to form the outer protective clear-coat layer which is approximately 0.5 mil thick.

Example 3

UV curable conductive composition 3 described above is applied by screen printing to a plastic sheet substrate. The conductive composition is irradiated with a UV gallium-doped metal halide lamp (curing energy approximately 350 mJ/cm²) for approximately 2 seconds to form an opaque conductive layer which is approximately 0.5 mil thick on the plastic sheet. UV curable dielectric composition 8 described above is next screen printed on the conductive layer. The dielectric composition is irradiated with the same UV lamp for approximately 2 seconds to form a dielectric layer which is approximately 0.3 mil thick. UV curable electroluminescent composition 1 described above is next screen printed on the dielectric layer. The electroluminescent composition is next irradiated with the same lamp for approximately 2 seconds to form an electroluminescent active layer which is approximately 1.5 mil thick. The electroluminescent active layer is next over-loaded by screen printing with UV curable transparent conductive composition 6 described above. The transparent conductive composition is next irradiated with the same UV lamp to form the transparent conductive layer which is approximately 0.8 mil thick. Finally, the electroluminescent lamp is completed by screen printing the clear-coat composition 9 onto the transparent conductive layer. The clear-coat is then irradiated with the same UV lamp to form the outer protective clear-coat layer which is approximately 0.5 mil thick.

Example 4

UV curable transparent conductive composition 6 described above is applied by screen printing to a plastic sheet substrate. The transparent conductive composition is irradiated with a UV gallium-doped metal halide lamp (curing energy approximately 350 mJ/cm²) for approximately 2 seconds to form a transparent conductive layer which is approximately 0.8 mil thick on the plastic sheet. UV curable dielectric composition 8 described above is next screen printed

on the transparent conductive layer. The dielectric composition is irradiated with the same UV lamp for approximately 2 seconds to form a dielectric layer which is approximately 0.8 mil thick. UV curable electroluminescent composition 1 described above is next screen printed on the dielectric layer. The
 5 electroluminescent composition is next irradiated with the same lamp for approximately 2 seconds to form an electroluminescent active layer which is approximately 1.5 mil thick. The electroluminescent active layer is next over-loaded by screen printing with UV curable opaque conductive composition 3 described above. The opaque conductive composition is next irradiated with the
 10 same UV lamp to form the conductive layer which is approximately 0.5 mil thick. Finally, the electroluminescent lamp is completed by screen printing the clear-coat composition 9 onto the transparent conductive layer. The clear-coat is then irradiated with the same UV lamp to form the outer protective clear-coat layer which is approximately 0.5 mil thick.

15

Example 5

UV curable opaque conductive composition 3 described above is applied by screen printing to a plastic sheet substrate. The composition is irradiated with a UV gallium-doped metal halide lamp (curing energy approximately 350 mJ/cm²) lamp for approximately 2 seconds to form an opaque conductive layer
 20 which is approximately 0.5 mil thick on the plastic sheet. UV curable electroluminescent composition 1 described above is next screen printed on the conductive layer. The electroluminescent composition is next irradiated with the same lamp for approximately 2 seconds to form an electroluminescent active layer which is approximately 1.5 mil thick. The electroluminescent active layer is next
 25 over-loaded by screen printing with UV curable transparent conductive composition 6 described above which is approximately 0.8 mil thick. The transparent conductive composition is next irradiated with the same UV lamp to form the transparent conductive layer. Finally, the electroluminescent lamp is completed by

screen printing the clear-coat composition 9 onto the transparent conductive layer. The clear-coat is then irradiated with the same UV lamp to form the outer protective clear-coat layer which is approximately 0.5 mil thick.

5 While embodiments of the invention have been illustrated and described, it is not intended that these embodiments illustrate and describe all possible forms of the invention. Rather, the words used in the specification are words of description rather than limitation, and it is understood that various changes may be made without departing from the spirit and scope of the invention.

5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210